

2J6024MPa

CELLULAR/LTE MIMO Adhesive/Magnetic Mount

Also available Adhesive (Pa) only or Magnetic (Ma) only

Key Features

Cable 1 - 2: CELLULAR / LTE

- 698-960 MHz
- 1710-2170 MHz
- 2500-2700 MHz

Adhesive/Magnetic Mount

Ground Plane Independent

Customizable Cable and Connector

Dimensions 80 x 76 x 13 mm



1. Antenna and electrical specifications

Cable 1

Parameters	CELLULAR / LTE Antenna		
Standards	2G,3G and 4G		
Band (MHz)	700/850/900	1700/1800/1900/2100	2600
Frequency (MHz)	698-960	1710-2170	2500-2700
Return Loss (dB)	~-10.0	~-7.8	~-9.7
VSWR	~2.2:1	~2.6:1	~2.1:1
Efficiency (%)	~25.3	~20.2	~36.1
Peak Gain (dBi)	~-0.7	~1.7	~4.4
Average Gain (dB)	~-6.1	~-7.1	~-4.4
Impedance (Ohm)	50		
Polarisation	Linear		
Radiation Pattern	Omni-Directional		
Max. Input Power (W)	25		
Connector Type	SMA-Male Standard (Other Connectors Available)		
Cable Length	300 cm Standard (Any Cable Length Available)		
Cable Type	D302 Standard (Other Cables Available)		

Cable 2

Parameters	CELLULAR / LTE Antenna		
Standards	2G,3G and 4G		
Band (MHz)	700/850/900	1700/1800/1900/2100	2600
Frequency (MHz)	698-960	1710-2170	2500-2700
Return Loss (dB)	~-9.9	~-8.3	~-9.1
VSWR	~2.5:1	~2.5:1	~2.2:1
Efficiency (%)	~25.7	~22.5	~35.2
Peak Gain (dBi)	~-0.8	~1.8	~4.5
Average Gain (dB)	~-6.1	~-6.6	~-4.6
Impedance (Ohm)	50		
Polarisation	Linear		
Radiation Pattern	Omni-Directional		
Max. Input Power (W)	25		
Connector Type	SMA-Male Standard (Other Connectors Available)		
Cable Length	300 cm Standard (Any Cable Length Available)		
Cable Type	D302 Standard (Other Cables Available)		

Antenna Measurement Conditions:

Mounted on 30 x 30 x 0.25 cm Metal Plate

200 cm of Cable D302



Measured in Certified CTIA 3D Anechoic Chamber




2. Mechanical and environmental specifications

Specifications	2J6024MPa
Mounting Type	Adhesive/Magnetic Mount, Also available Adhesive (Pa) only or Magnetic (Ma) only
Dimensions (mm)	80 x 76 x 13
Radome	ASA
Radome color	Black
Operating Temperature (C)	-40 to +85
Storage Temperature (C)	-40 to +85
Substance Compliance	RoHS



3. Antenna parameters




Cable 1: CELLULAR/LTE






Cable 2: CELLULAR/LTE







ISOLATION FOR CABLES 1 AND 2




ENVELOPE CORRELATION COEFFICIENT FOR CABLES 1 AND 2






Radiation pattern reference


Cable 1: CELLULAR/LTE




750 and 850 MHz Radiation pattern



940 and 1750 MHz Radiation pattern




1850 and 1950 MHz Radiation pattern




2100 and 2600 MHz Radiation pattern


Cable 2: CELLULAR/LTE




750 and 850 MHz Radiation pattern



940 and 1750 MHz Radiation pattern





1850 and 1950 MHz Radiation pattern




2100 and 2600 MHz Radiation pattern

4. Antenna drawings



2J6024MPa - Magnetic Mount version



2J6024MPa - Adhesive Mount version

5. Antenna Images

