


2JF0515P

915MHz ISM Flexible Polymer

Key Features

- 915 MHz ISM
- 902-928 MHz
- Self-Adhesive
- Flexible Material
- Ground Plane Independent
- Customized Cable and Connector
- Dimensions 39.9 x 7.0 x 0.2 mm



1. Antenna and electrical specifications

Parameters	915 MHz ISM Antenna
Standards	ZigBee, ISM, SigFox, LoRa
Band (MHz)	915 MHz
Frequency(MHz)	902-928
Return Loss (dB)	~-17.6
VSWR	~1.3:1
Efficiency (%)	~33.6
Peak Gain (dBi)	~0.3
Average Gain (dB)	~-4.7
Impedance (Ohm)	50
Polarization	Linear
Radiation Pattern	Omni-Directional
Max. Input Power (W)	25
Connector Type	U.FL Standard (Other Connectors Available)
Cable Length	100mm Standard (Any Cable Length Available)
Cable Type	1.37mm Mini-Coax Standard (Other Cables Available)

Antenna Measurement Conditions:

Mounted on 30 x 30 x 0.25 cm ABS Plate



100 mm 1.37 mm Cable



Measured in Certified CTIA 3D Anechoic Chamber



2. Mechanical and environmental specifications

Specifications	2JF0515P
Mounting Type	Self-Adhesive
Dimensions (mm)	39.9 x 7.0 x 0.2
Material	Flexible Polymer
Operating Temperature (C)	-40 to +85
Storage Temperature (C)	-40 to +85
Substance Compliance	RoHS


3. Antenna parameters








Radiation pattern reference



915 MHz Radiation pattern

4. Antenna drawings



5. Antenna Images

